

CL Copper Lugs

GENERAL PROPERTIES :

Red2go Copper Lugs are made from 99.9% high copper conductivity annealed copper which gives excellent electrical properties.

CONFORMANT STANDARDS:

SANS IEC 1238-11993

BASIC DIMENSIONS:

Part Number	DESCRIPTION	Length	I.D
CL1.5-5	Copper Lug 1.5mm ² Cable - 5mm Stud	19.1	2.1
CL1.5-6	Copper Lug 1.5mm ² Cable - 6mm Stud	26.6	2.1
CL2.5-4	Copper Lug 2.5mm ² Cable - 4mm Stud	21.4	2.5
CL2.5-5	Copper Lug 2.5mm ² Cable - 5mm Stud	21.4	2.5
CL2.5-6	Copper Lug 2.5mm ² Cable - 6mm Stud	26.2	2.5
CL2.5-8	Copper Lug 2.5mm ² Cable - 8mm Stud	26.2	2.5
CL4-5	Copper Lug 4mm ² Cable - 5mm Stud	21.0	3.3
CL4-6	Copper Lug 4mm ² Cable - 6mm Stud	27.8	3.3
CL4-8	Copper Lug 4mm ² Cable - 8mm Stud	28.6	3.3
CL6-5	Copper Lug 6mm ² Cable - 5mm Stud	23.0	3.7
CL6-6	Copper Lug 6mm ² Cable - 6mm Stud	27.0	3.7
CL6-8	Copper Lug 6mm ² Cable - 8mm Stud	28.6	3.7
CL6-10	Copper Lug 6mm ² Cable - 10mm Stud	28.6	3.7
CL10-5	Copper Lug 10mm ² Cable - 5mm Stud	27.0	4.7
CL10-6	Copper Lug 10mm ² Cable - 6mm Stud	29.4	4.7
CL10-8	Copper Lug 10mm ² Cable - 8mm Stud	28.6	4.7
CL10-10	Copper Lug 10mm ² Cable - 10mm Stud	30.6	4.7
CL10-12	Copper Lug 10mm ² Cable - 12mm Stud	33.0	4.7
CL16-6	Copper Lug 16mm ² Cable - 6mm Stud	39.7	5.5
CL16-8	Copper Lug 16mm ² Cable - 8mm Stud	39.7	5.5
CL16-10	Copper Lug 16mm ² Cable - 10mm Stud	41.5	5.5
CL16-12	Copper Lug 16mm ² Cable - 12mm Stud	46.0	5.5
CL25-6	Copper Lug 25mm ² Cable - 6mm Stud	43.6	7.1
CL25-8	Copper Lug 25mm ² Cable - 8mm Stud	43.6	7.1
CL25-10	Copper Lug 25mm ² Cable - 10mm Stud	43.6	7.1
CL25-12	Copper Lug 25mm ² Cable - 12mm Stud	51.0	7.1
CL35-6	Copper Lug 35mm ² Cable - 6mm Stud	43.6	8.4
CL35-8	Copper Lug 35mm ² Cable - 8mm Stud	43.6	8.4
CL35-10	Copper Lug 35mm ² Cable - 10mm Stud	43.6	8.4
CL35-12	Copper Lug 35mm ² Cable - 12mm Stud	51.2	8.4
CL50-6	Copper Lug 50mm ² Cable - 6mm Stud	51.6	9.5
CL50-8	Copper Lug 50mm ² Cable - 8mm Stud	51.6	9.5

CL50-10	Copper Lug 50mm ² Cable - 10mm Stud	51.6	9.5
CL50-12	Copper Lug 50mm ² Cable - 12mm Stud	51.6	9.5
CL70-6	Copper Lug 70mm ² Cable - 6mm Stud	54.0	11.0
CL70-8	Copper Lug 70mm ² Cable - 8mm Stud	54.0	11.0
CL70-10	Copper Lug 70mm ² Cable - 10mm Stud	54.0	11.0
CL70-12	Copper Lug 70mm ² Cable - 12mm Stud	54.0	11.0
CL70-16	Copper Lug 70mm ² Cable - 16mm Stud	54.2	11.0
CL95-8	Copper Lug 95mm ² Cable - 8mm Stud	57.2	13.4
CL95-10	Copper Lug 95mm ² Cable - 10mm Stud	57.2	13.4
CL95-12	Copper Lug 95mm ² Cable - 12mm Stud	57.2	13.4
CL95-16	Copper Lug 95mm ² Cable - 16mm Stud	75.5	13.4
CL120	Copper Lug 120mm ² Cable - Blank Palm	68.3	15.5
CL120-8	Copper Lug 120mm ² Cable - 8mm Stud	68.3	15.5
CL120-10	Copper Lug 120mm ² Cable - 10mm Stud	68.3	15.5
CL120-12	Copper Lug 120mm ² Cable - 12mm Stud	68.3	15.5
CL120-16	Copper Lug 120mm ² Cable - 16mm Stud	68.3	15.5
CL150-10	Copper Lug 150mm ² Cable - 10mm Stud	75.0	16.3
CL150-12	Copper Lug 150mm ² Cable - 12mm Stud	75.0	16.3
CL150-16	Copper Lug 150mm ² Cable - 16mm Stud	75.0	16.3
CL185-10	Copper Lug 185mm ² Cable - 10mm Stud	79.0	18.4
CL185-12	Copper Lug 185mm ² Cable - 12mm Stud	79.0	18.4
CL185-16	Copper Lug 185mm ² Cable - 16mm Stud	79.0	18.4
CL240	Copper Lug 240mm ² Cable - Blank Palm	127.0	21.2
CL240-10	Copper Lug 240mm ² Cable - 10mm Stud	127.0	21.2
CL240-12	Copper Lug 240mm ² Cable - 12mm Stud	127.0	21.2
CL240-16	Copper Lug 240mm ² Cable - 16mm Stud	127.0	21.2
CL300	Copper Lug 300mm ² Cable - Blank Palm	127.0	23.8
CL300-10	Copper Lug 300mm ² Cable - 10mm Stud	127.0	23.8
CL300-12	Copper Lug 300mm ² Cable - 12mm Stud	127.0	23.8
CL400	Copper Lug 400mm ² Cable - Blank Palm	123.0	26.9
CL400-10	Copper Lug 400mm ² Cable - 10mm Stud	123.0	26.9
CL400-12	Copper Lug 400mm ² Cable - 12mm Stud	123.0	26.9
CL500	Copper Lug 500mm ² Cable - Blank Palm	142.0	30.0
CL500-12	Copper Lug 500mm ² Cable - 12mm Stud	142.0	30.0
CL630	Copper Lug 630mm ² Cable - Blank Palm	146.0	33.5
CL630-12	Copper Lug 630mm ² Cable - 12mm Stud	146.0	33.5

The above information corresponds to our actual knowledge and are according to our knowledge is rendered correct and reliable. But they do not represent binding properties. Customers and end-users have to decide autonomously about application in the provided range. Under no circumstances is Red2go Pty Ltd liable for any eventual, indirect or consequential damages arising from the sales, resales, transfer, use or misuse of the product. Our Liabilities are limited to only in replacing products due to manufacturing defects.